

## PRODUCT DATA SHEET

### KEWISO4

#### KT1720

- Five voltage ranges
- 12 - 50 - 120 - 230 - 400V AC/DC
- Compact design encourages safe site use
- No batteries required
- Separate lamps indicate AC or DC with polarity
- Retractable probe shrouds with slim tip design to fit into push fit connector blocks
- Permanent GS38 compliance
- BSEN 61243-3:2010
- EN61010 CATIV 600V
- BSEN 613 26-1:2010
- Double insulated leads 1.4m long
- Dual LEDS for each voltage level indication
- Ergonomic design is comfortable to hold and suitable for use with gauntlets / PPE equipment

#### KEWPROVE3

- High output 690 V AC/DC
- Steps down voltage levels
- Essential for proving your two-pole voltage tester

#### KEWLOK

- One size fits all MCBs and most toggle main switches
- No need for separate lock and no keys required
- User selectable integral combination padlock
- Comes with two warning labels

### KEWISO4 INCLUDES:

- KT1720 Two-pole voltage tester
- KEWPROVE3 High output proving unit
- KEWLOK Universal Lock Off device
- Carry Case with access to proving unit

### PRODUCT INFO

- 117 x 90 x 320 Boxed (WxDxH mm)
- 810g Weight
- EAN 5060084081901

## KEWISO4

### Safe Isolation Kit



### KT1720 SPECIFICATION

Voltage Range	12 - 50 - 120 - 230 - 400V AC/DC
Voltage Category	CAT IV 600V
Operating current	Less than 3.5mA (Conforms to BSEN 61010)
Cable	Double insulated silicone 1.4metres
Power Supply	Self powered from voltage source, no batteries required
Duty cycle	2 minutes on 10 minutes off for voltages above 330V

kewtechcorp.com

0345 646 1404

sales@kewtechcorp.com