



PRODUCT DATA SHEET

KEWIS03

KT1795

- AC voltage range 6 V - 1000 V
- DC voltage range 6 V - 1500 V
- Single pole voltage detection on both probes
- Phase rotation - bright green LEDs show left or right rotation
- Ghost voltage clearance feature
- 1 V LCD resolution display
- Continuity & Resistance with LCD readout
- Self-diagnostic test
- Bright LEDs indicate voltage level
- Clear audible tone & bright torch
- Diode test & polarity indication

KEWPROVE3

- High output 690 V AC/DC
- Steps down voltage levels
- Essential for proving your two-pole voltage tester

KEWLOK

- One size fits all MCBs and most toggle main switches
- No need for separate lock and no keys required
- Comes with two warning labels
- User selectable integral combination padlock

KEWIS03 INCLUDES

- KT1795 Two-pole voltage & continuity tester
- KEWPROVE3 High output proving unit
- KEWLOK Universal Lock Off device
- Carry Case with access to proving unit

PRODUCT INFO

- 117 x 90 x 320 Boxed (WxDxH mm)
- 885g Weight
- EAN 5060084081970

KEWIS03

Safe Isolation Kit



KT1795 SPECIFICATION

VOLTAGE TEST

LED nominal Voltage	12/24/50/120/230/400/690/ 1000V, AC (40...400Hz), DC(±)
LED tolerances	EN 61243-3
ELV indication LED	>50VAC, >120V DC
Response time	<1s at 100% of each nominal value
LCD Range	6...1000VAC, 1500VDC(±)
LCD Resolution	1V
LCD Accuracy	±3%±3dgt (6...1000VAC/1500Vdc)
LCD Overrange indication	"OL"
Peak current with push buttons not pressed	I _s <3.5mA (at 1000V)
Peak current with push buttons pressed	I _s <300 mA
Measurement Duty	30 s ON, 240 s OFF

SINGLE POLE PHASE TEST

Voltage Range	100...1000V AC (50/60Hz)
---------------	--------------------------

PHASE ROTATION TEST

System	170...1000V phase-to-phase, AC 50/60Hz
--------	--

CONTINUITY TEST

Continuity test range	0...500kΩ + 50%
Resistance measurement	0-1999Ω ±(5% + 10dgt); Resolution: 1Ω

GENERAL

Temperature	-5...40°C operation; -20...70°C storage; No condensation
Humidity	max. 85% RH
Altitude	up to 2000 m
Overvoltage	CAT. III 1000V/ CAT. IV 600V
Standard	BS EN 61243-3:2014
Pollution	Degree 2
Protection	IP64
Battery	3V (IEC LR03 1.5V x 2)
Internal battery consumption	approx. 80mA

kewtechcorp.com

0345 646 1404

sales@kewtechcorp.com