

PRODUCT DATA SHEET

KT64DL

MULTIFUNCTION TESTER WITH EV

- Easy to use
- Anti Trip Technology loop test - for full no trip Loop testing on RCDs of all types.
- Low susceptibility to RCD uplift and noise interference
- Displays PFC/PSC at same time as Loop reading
- 250 / 500 / 1000V insulation test with auto discharge
- SPD testing
- Test leads auto-null for continuity mode
- RCD test type A, AC, AS, ACS, auto & ramp
- 6mA DC test at 0 & 180 for EV charge point testing
- New design ultra slim probe tips for access to push fit connector blocks
- Hand-free mode controlled by separate button
- Single rotary dial for function selection
- Mains polarity test

INCLUDED ACCESSORIES

- ACC063 distribution board test lead set
- Kamp 12 mains lead
- Batteries
- Printed Instruction Manual
- End of line Calibration Certificate
- Soft carry case

OPTIONAL

- KEWEVA Testing Adapter
- FC2000 calibration checker
- Lightmate kit – for fast connection to light fittings
- Pat Adaptor1 – converts your KT64DL into a Pat Tester
- Jump1d1 – Small jump leads for 18th edition cont/ins testing

PRODUCT INFO

- 313 x 200 x 200 Boxed (WxDxH mm)
- 2.32kg Weight
- EAN 5060084082816
- Made in China

KT64DL

The UK's smallest MFT with EV testing



SPECIFICATIONS

EV

SPD

CONTINUITY

Open Circuit Voltage (DC)	Short Circuit Current	Ranges (Auto Range)	Accuracy
>4V, <10V	>200mA	9.99Ω, 99.9Ω, 29.99 kΩ	±3% ±2 digits

Test Lead Null 4Ω, Hazard warning LED >25V, Typical Test Time(2Ω) <2 sec

INSULATION

Open Circuit Voltage (DC)	Output Current	Ranges (Auto Range)	Accuracy
250V	1mA - 0 = + 20% @ 250kΩ	9.99MΩ, 99.9MΩ, 2000MΩ	±3% ±1 digits ±6% ±1 digits
500V	1mA - 0 = + 20% @ 500kΩ	9.99MΩ, 99.9MΩ, 199MΩ, 2000MΩ	±3% ±1 digits ±6% ±1 digits
1000V	1mA - 0 = + 20% @ 1MΩ	9.99MΩ, 99.9MΩ, 399MΩ, 2000MΩ	±3% ±1 digits ±6% ±1 digits

Short circuit current (in to 2kΩ) <2mA, Typical Test Time (10MΩ) <2 sec

BREAKDOWN VOLTAGE / SPD

Range	Measurement Range	Accuracy	I limit detection	Voltage increment
1000 V	0 - 105	+5% +5digits	1mA	1 volt at 100V per sec

LOOP IMPEDANCE

Range	Accuracy
ATT No trip 0.00 – 9.99 Ω	± 5% ± 5 digits
ATT No trip 10.00 – 99.9 Ω	± 3% ± 3 digits
ATT No trip 100 - 500 Ω	± 3% ± 3digits
High Current 0.000 - 500 Ω	± (3% + 30mΩ)

PSC/PFC

PSC accuracy is derived from measured loop impedance specification and measured voltage specification.

Voltage measurement: +/- 3% 50/60Hz and 90 – 250V

RCD (Type AC, ACS, A, AS)

Function	Accuracy	Rated Voltage	Tripping Time Accuracy	
X ½	−0% to −10%	195V – 253V AC 50Hz	Up to 1 second	±(1% + 1ms)
X 1	+0% to +10%		Above 1 second	±(1% +10ms)
X 5	+0% to +10%			
Ramp Test	Increments in 3mA steps			
Auto test	30mA RCD	½ x 0°, ½ x 180 °, 1 x 0°, 1 x 180 °, 5 x 0°, 5x 180 °		
EV RDC-DD	6mA (-0% +13%)			

kewtechcorp.com

0345 646 1404

sales@kewtechcorp.com